

MENU

MENU VMOD 150HD

PRODUCTION

- SELECT PRODUCTION
 - [NAME] [ID]
- NEW PRODUCTION
 - [NAME] [ID]
- DELETE PRODUCTION
 - [NAME] [ID]
- DEV. WRITEPROT.
 - Select ID [XX]
 - *WP DISABLE
 - WP ENABLE
- AUTONAMING
 - *DISABLE
 - ENABLE
- SUB CARRIER
 - *0....359
- EE MODE
 - *DISABLE
 - ENABLE
- ANALOG TEST
 - *DISABLE
 - ENABLE

VIDEO

- VIDEO INPUT
 - *COMPOSIT
 - Y/C
 - REF.
- VIDEO REF.
 - *INTERN
 - EXT.REF
 - MIXING REF
 - INPUT
- BURST REF.
 - *INTERN
 - VIDEO REF.
- HOR. OFFSET
 - 19...*0...+19
- NTSC TC
 - *30 NON DF
 - 30 DROP FR
 - AUTO
- STILL MODE
 - *ANY FIELD
 - ODD ONLY
 - EVEN ONLY
 - ODD FIRST
 - EVEN FIRST

AUDIO

- AUDIO IN GAIN
 - Audio 1 In: -9...*0...13,5db
 - Audio 2 In: -9...*0...13,5db
 - Audio 3 In: -9...*0...13,5db
 - Audio 4 In: -9...*0...13,5db
- AUDIO OUT GAIN
 - Audio 1 Out: *0....-21db
 - Audio 2 Out: *0....-21db
 - Audio 3 Out: *0....-21db
 - Audio 4 Out: *0....-21db
- SHUTTLE AUDIO
 - *DISABLE
 - ENABLE
- RS422 EMULATION
 - *[F0] [32]
- SCSI SERVERMODE
 - *DISABLE
 - ENABLE
- SLOMO SPEED
 - SloMo *00..99 %

SYSTEM

- INIT DEVICE
 - Select ID: [XX]
 - *PAL
 - NTSC
 - *Audio Tracks 4
 - Audio Disable
 - Audio Tracks 1
 - Audio Tracks 2
 - Audio Tracks 3
 - *48,0 kHz
 - 32,0 kHz
 - 44,1 kHz
 - Benching [XX]... *2,0/1.. [XXmXXs] ...33,0/1 [XXmXXs]
 - Init [XX]: No/Yes
 - with Format: No/Yes
- DISPLAY TC
 - *ABS
 - LTC
 - LTC READER
 - VITC
 - BIPHASE
 - MASTER
- RECORD
 - *ENABLE
 - DISABLE
 - STAY on LAST
- LOOP
 - LOOP MODE
 - *DISABLE
 - LOOP
 - LIST ONCE
 - LIST LOOP
 - LOOP IN TC
 - 00:00:00:00
 - LOOP OUT TC
 - 00:00:00:00
 - LIST EDIT
 - OETICS TC
 - *MEDIAMODE
 - CLIPMODE
- SETUP DEFAULTS
 - SURE? NO / YES
 - POWER OFF
- EDIT SELECT
 - *ODD FIELD
 - EVEN FIELD
- SUREFACE CHECK
 - SELECT ID [XX]
 - sec: xxxxxxxx
- SPEED LIMIT
 - 10x...*300x

MASTER

- REMOTE 1
 - *COM 3
 - COM 4
 - COM 5
 - COM 1
 - TCP / IP
 - REM TC
- REMOTE 2
 - *DISABLE
 - COM 3
 - COM 4
 - COM 5
 - COM 1
 - TCP / IP
 - REM TC
- CHASE MODE
 - *DISABLE
 - ENABLE
- REM. TC
 - *LTC READER
 - BIPHASE
 - AUTO TC
- PROG REC.
 - IN: 00:00:00:00
 - OUT: 00:00:00:00
 - PREROLL: 00:00:00:00
 - POSTROLL: 00:00:00:00
- COM DEVICE

SET COM 3	SET COM 4	SET COM 5	SET COM 1	SET TCI / IP PRO	SET TCI / IP ID
*RS422 DEVICE	*RS422 DEVICE	*RS422 DEVICE	*RS422 DEVICE	*RS422 DEVICE	*192.168.001.001
PIONEER LD	PIONEER LD	PIONEER LD	PIONEER LD	PIONEER LD	
VMOD Remote	VMOD Remote	VMOD Remote	VMOD Remote	VMOD Remote	
Win Taker	Win Taker	Win Taker	Win Taker	Win Taker	
FEG 38,4 kB	FEG 38,4 kB	FEG 38,4 kB	FEG 38,4 kB	FEG 38,4 kB	
FEG 19,2 kB	FEG 19,2 kB	FEG 19,2 kB	FEG 19,2 kB	FEG 19,2 kB	
gtc Taker	gtc Taker	gtc Taker	gtc Taker	gtc Taker	
RS422 CONTR.	RS422 CONTR.	RS422 CONTR.	RS422 CONTR.	RS422 CONTR.	
RS232 X POINT	RS232 X POINT	RS232 X POINT	RS232 X POINT	RS232 X POINT	
DISABLE	DISABLE	DISABLE	DISABLE	DISABLE	
- ADD ENTRY
 - IN 00:00:00:00
 - OUT 00:00:00:00
- EDIT ENTRY
 - 001) [ID] [name]
 - IN 00:00:00:00
 - OUT 00:00:00:00
- DEL ENTRY
 - 001) [ID] [name]
 - IN 00:00:00:00
 - OUT 00:00:00:00
- CLEAR LIST
 - CLEAR LIST NO
 - CLEAR LIST YES

INSERTER

- INSERTER MODE
 - *DISABLE
 - SMALL
 - LARGE
- POSITION
 - *COL:100 ROW :100
- INSERTER COLOR
 - *WHITE ON BLACK
 - BLACK ON WHITE
 - WHITE ON BKGD
 - BLACK ON BKGD

TC-READER

- VITC
 - LINE 1: 10....40
 - LINE 2: 10....40
 - HS FILTER:
 - *DISABLE
 - ENABLE
 - BIPHASE
 - *25 / 30 Hz
 - 50 / 60 Hz
 - BIPHASE ABS:
 - *00:00:00:00

GENERATOR

- LTC
 - OFFSET: *00:00:00:00
 - GAIN: 24...*0...9dB
- VITC
 - OFFSET: *00:00:00:00
 - LINE 1: 10....40
 - LINE 2: 10....40

INFO

- DEVICE
 - Select ID [XX]
 - DEVICE: VENDOR: MODEL: REV.: SIZE:
- VERSION
 - VMOD 201
 - VERSION: 1.157 / 2.0.33
 - BUILD: Mar.09.2001
- HARDWARE
 - PANEL: F7
 - VIDEO: 04FF
 - AUDIO: 0000

STEENBECK
digital

* Default entry